

(11) Publication number : **0 326 265 B1**

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification :
25.11.92 Bulletin 92/48

(51) Int. Cl.⁶ : **B60N 2/26**

(21) Application number : **89300396.2**

(22) Date of filing : **17.01.89**

(54) **Child's safety seat.**

(30) Priority : **26.01.88 GB 8801716**

(43) Date of publication of application :
02.08.89 Bulletin 89/31

(45) Publication of the grant of the patent :
25.11.92 Bulletin 92/48

(84) Designated Contracting States :
DE ES FR GB IT NL SE

(56) References cited :
EP-A- 0 155 784
EP-A- 0 200 411
EP-A- 0 287 259
DE-A- 1 430 468
FR-A- 2 123 701

(73) Proprietor : **BRITAX-EXCELSIOR LIMITED**
1 Churchill Way West
Andover, Hampshire SP10 3UW (GB)

(72) Inventor : **Burleigh, David William**
65 Craigwell Lane Aldwick
Bognor Regis West Sussex (GB)
Inventor : **Assinder, Andrew John**
47 Crossbush Road Summerley
Bognor Regis West Sussex, PO22 7LT (GB)

(74) Representative : **Hollinghurst, Antony**
B.S.G. International plc Patent Department
Castle Trading Estate East Street
Portchester, Hampshire PO16 9SD (GB)

EP 0 326 265 B1

Note : Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

1

EP 0 326 265 B1

2

Description

This invention relates to a child's safety seat of the type having an adult seat belt with a shoulder portion and a lap portion, the child's seat comprising a seat body having a seat portion, a back rest and vertically extending side walls projecting forwardly from the side edges of the back rest, together with first and second guide means adjacent to the junction between the seat portion and the back rest for locating the lap portion of the adult seat belt, a head rest mounted on the back rest, and third guide means for the shoulder portion of an adult seat belt positioned so as to guide said shoulder portion of the adult belt between the back rest and the head rest.

A child's seat of this type is disclosed in EP-A-0 155 784. The headrest incorporates an upper backrest portion which is mounted on a lower backrest portion by dowels and the third guide means takes the form of a projecting wing on the headrest.

According to the invention, in a child's safety seat of this type, the head rest is mounted on the back rest by means permitting adjustment of the distance between the head rest and the seat portion, and the third guide means includes means for restricting movement of the shoulder portion of said adult seat belt relative to the third guide means in the transverse direction of the belt.

Embodiments of the invention will now be described, by way of example with reference to the accompanying drawings, in which:-

Figure 1 is a perspective view of a child's safety seat in accordance with a first embodiment of the invention, secured by an adult seat belt on the right-hand side of a motor car;

Figure 2 is a schematic transverse cross-sectional view of the seat shown in Figure 1;

Figure 3 is a side view of the third guide means of the seat shown in Figures 1 and 2 in the released position;

Figure 4 is a cross-sectional view taken on the line 4 - 4 in Figure 3 but showing the guide means in the secured position;

Figure 5 is a perspective view, similar to Figure 1, of a second embodiment of the invention, with the head rest in its highest position;

Figure 6 is a cross-sectional view taken on the line 6 - 6 in Figure 5 but showing the guide means in the secured position;

Figure 7 is a cross-sectional view taken on the line 7 - 7 in Figure 6; and

Figure 8 is a scrap view in the direction of the arrow 8 in Figure 7.

Referring to Figure 1, a child's safety seat comprises a seat body 10 having a seat portion 12 with side walls 14 and 16 forming arm rests, and a back rest 18 with side walls 20 and 22. Notches 24 and 26, formed between the side walls 14, 20, and 16, 22 re-

spectively form first and second guide means for the lap portion 28 of an adult seat belt which is secured by a buckle 29.

A head rest 30, having side wings 32 and 34 is mounted on a pair of inverted U-shaped slide bars 36 and 38, one end of each slide bar 36, 38 being embedded in the head rest 30. The other end of each slide bar 36, 38 projects through a respective opening 40 in the top edge of the back rest 18 and downwardly into frictional engagement with a respective bush 42 secured to the back of the back rest 18 (only the bush 42 for the slide bar 36 being visible in Figure 2). The vertical position of the head rest 30 relative to the back rest 18 can be adjusted by sliding the slide bars 36 and 38 through their respective bushes 42, the bottom of the head rest 30 being in front of the back rest 18 and the side walls 32 and 34 thereof between the side walls 20 and 22 of the back rest 18.

The side wall 32 of the head rest 30 has a rearwardly and/or inwardly facing belt guide hook 44 projecting from its lower edge. A belt guide clamp 46 is mounted on the upper edge of the adjacent back rest side wall 20. The shoulder portion 48 of the adult seat belt, which extends from the buckle 30 to a shoulder anchorage 50, passes through the guide hook 44 and the guide clamp 46 as illustrated. In order to permit the seat 10 to be used on the left-hand side of the car, a second guide hook (not shown) is mounted on the bottom edge of the opposite side wall 34 of the head rest 30 and a second guide clamp 52 is mounted on the top of the adjacent back rest side wall 22 (Figure 1).

Figures 3 and 4 illustrate the belt clamp 46 in more detail. The clamp 46 is formed as a one-piece plastics moulding, consisting of a base portion 50 connected at one end to a lever portion 52 by an integral hinge 54. The base portion 50 has a longitudinally extending central rib 56 while the lever portion 52 has two mutually parallel ribs 58 and 60 which are positioned one on each side of the rib 56. At the opposite end to the hinge 54, the base portion has a resilient catch 62 which can be brought into engagement with a projection 64 on the corresponding end of the lever portion 52.

When the lever portion 52 is positioned parallel to the base portion 50, with the catch 62 engaged, the three ribs 56, 58 and 60 define a sinuous path for the belt 48 of sufficiently high friction to resist retraction of the seat belt by its emergency locking retractor (not shown) below the shoulder anchorage 50. A stud 66 on the end of the rib 56 nearer to the catch 62 engages in a recess 68 in the lever portion 52 so as to prevent the belt 48 from slipping out sideways. Provided that the headrest 30 is correctly positioned for a particular seat occupant, the shoulder belt 48 will be correctly positioned across the occupant's torso.

Figures 5 to 8 illustrate a second embodiment of the invention comprising a seat body 70, similar to the seat body 10 of Figure 1, formed as a one-piece plas-

3

EP 0 326 265 B1

4

tics moulding and having a seat portion 72 with side walls 74 and 76 forming arm rests, and a back rest 78 with side walls 80 and 82. Notches 84 and 86, formed between the side walls 74, 80, and 76, 82 respectively form first and second guide means for the lap portion 28 of the adult seat belt. The shoulder portion 48 of the adult seat belt is not shown in Figures 6 and 8.

A head rest 90, formed as a one-piece plastics moulding and having side wings 92 and 94 is mounted on a pair of slide tracks 96 and 98 which are recessed into the back rest 78 adjacent to its junctions with the side wings 80 and 82 respectively. As can be seen from Figures 6 and 7, the track 96 consists of a channel-like metal pressing having side flanges 100 and 102 which abut against walls of a recess 104 in the back of the back rest 78, and upper and lower end tabs 106 and 108 which are secured to the back rest 78 by rivets 110 and 112 respectively.

Between the flanges 100 and 102, the track 96 is generally U-shaped, and has a central vertically extending slot 114 which is engaged by a slide shoe formed from interlocking rear and front parts 116 and 118. The rear slide shoe part 116 is of generally T-shaped cross-section, having its cross-bar located on the rear side of the track 96 and its stem projecting through the slot 114 into a recess in the front slide shoe part 118 on which the head rest 90 is mounted, the two slide shoe parts 116 and 118 and the head rest 90 being held together by a bolt 120.

The lower part 122 of the side wing 92 of the head rest 90, which abuts against the front slide shoe part 118, is inclined to the upper part, as can be seen in Figure 7. The lower part 122 contains a slot 124, which is somewhat wider than the adult safety belt and which has a branch slot 126 permitting the shoulder part 48 of the adult safety belt to be inserted therein. The front slide shoe part 118 contains a slot 128 which is aligned with the slot 124 and has its bottom side aligned with the bottom of the slot 124, but is broader in the vertical direction. In its upper edge, the slot 128 contains a groove 130 which accommodates a locking cam bar 132. The cam bar 132 is dimensioned to allow space for the shoulder part 48 of the adult seat belt to pass between it and the bottom of the slot 128 and its upper edge is convex so that it can rock against the top of the groove 130. The bottom edge of the cam bar 132 is angled so that the cam bar rocks rearwardly in the event that tension is applied to the upper end of the shoulder part 48 of the adult belt, allowing the latter to move freely through the slots 124 and 128, but rocks into a wedging position if any attempt is made to pull the adult belt through the grooves 124 and 128 in the opposite direction.

The side wall 94 and the track 98 on the other side of the head rest 90, together with the associated slide shoe parts, are a mirror image of the side wall 92, the slide guide 96 and the slide shoe parts 116 and 118. Where visible, they are denoted by the same refer-

ence numerals.

In use, the seat is located on an adult vehicle seat with the head rest 90 either at the required height for the child who is to occupy the seat or at a higher position. The child is then placed on the seat, the adult seat belt secured by the buckle 29 and the shoulder portion 48 thereof inserted into one of the slots 124. The height of the head rest 90 is then adjusted, if necessary. Finally, any slack in the adult seat belt is pulled through the slots 124 and 128 so that the child seat is securely held in position by the lap portion 28 of the adult seat belt. The cam bar 32 prevents any slack being fed back through the slots 124 and 128 which could otherwise cause the lap portion 28 to slacken. The head rest 90 is retained in its set position on the tracks 96 by friction.

The belt clamp of Figures 3 and 4 may be used with the seat shown in Figure 5. Similarly, the clamp incorporating the cam bar 132 of Figure 7 may be used with the seat shown in Figure 1.

Claims

1. A child's safety seat for fitting to a vehicle seat having an adult seat belt with a shoulder portion (48) and a lap portion (28), the child's seat comprising a seat body (10, 70) having a seat portion (12, 72), a back rest (18, 78) and vertically extending side walls (20, 22; 80, 82) projecting forwardly from the side edges of the back rest (18, 78), together with first and second guide means (24, 26; 84, 86) adjacent to the junction between the seat portion (12, 72) and the back rest (18, 78) for locating the lap portion (28) of the adult seat belt, a head rest (30, 90) mounted on the back rest (18, 78), and third guide means (44, 46; 124, 128) for the shoulder portion (48) of an adult seat belt positioned so as to guide said shoulder portion (48) of the adult belt between the back rest (18, 78) and the head rest (30, 90), characterised in that the head rest (30, 90) is mounted on the back rest (18, 78) by means permitting adjustment of the distance between the head rest (30, 90) and the seat portion (12, 72), and the third guide means (44, 46; 124, 128) includes means (44, 124) for restricting movement of the shoulder portion (48) of said adult seat belt relative to the third guide means (44, 46; 124, 128) in the transverse direction of the belt.
2. A child's safety seat according to claim 1, wherein the third guide means (44, 46; 124, 128) includes blocking means for restricting movement of the shoulder portion (48) of said adult seat belt relative to the third guide means (44, 46; 124, 128) in the longitudinal direction of the belt.

3

5

EP 0 326 265 B1

6

3. A child's safety seat according to claim 2, wherein the blocking means comprises a wedging cam (132) arranged to inhibit movement of the shoulder portion (48) of said adult seat belt through the third guide means (124, 128) in one direction while allowing movement in the opposite direction. 5
4. A child's safety seat according to claim 2, wherein at least part (46) of the third guide means (44, 46) comprises first and second pivotally interconnected base portions (50, 52), a pair of spaced parallel formations (58, 60) on the second base portion (52) and a complementary formation (56) on the first base portion (50) arranged so as to lie between the parallel formations (58, 60) so as to define a sinuous path therebetween when the first and second base portions (50, 52) are in a first relative angular position and to be clear of the parallel formations (58, 60) when the first and second base portions (50, 52) are in a second angular position, together with catch means (62, 64) for securing the first and second base portions (50, 52) in their first relative angular position. 10 15 20
5. A child's safety seat according to any of claims 1 to 4, wherein the headrest has a pair of side walls (32, 34; 92, 94) and at least part (44; 124, 128) of the third guide means (44, 46; 124, 128) is mounted on one of the side walls (32, 34; 92, 94). 25 30
6. A child's safety seat according to any of claims 1 to 5, wherein fourth guide means (44, 46; 124, 128) similar to the third guide means (44, 46; 124, 128), is mounted on the other side wall of the head rest (30, 90). 35
7. A child's safety seat according to any of claims 1 to 6, wherein the head rest (30) is mounted on the seat body (10) by two U-shaped slide bars (36, 38), one limb of each slide bar (36, 38) being embedded in the head rest (30) and the other limb engaging in guide means (42) in the back rest (18). 40
8. A child's safety seat according to any of claims 1 to 6, wherein the head rest (90) has two slide shoes (116) each of which engages in a respective slide track (96, 98) which is recessed into the back rest (78). 45 50
9. A child's safety seat according to claims 3 and 8, wherein the third guide means (124, 128) includes a slot (128) in of one of the slide shoes (116), the wedging cam (132) being located in said slot (128). 55

Patentansprüche

1. Kinder-Sicherheitssitz zum Einsetzen in einen mit einem Erwachsenen-Sicherheitsgurt mit Schulterteil (48) und Hüftteil (28) versehenen Fahrzeugsitz, umfassend: einen Sitzkörper (19, 70) mit einem Sitzflächenteil (12, 72), einer Rückenlehne (18, 78) und sich vertikal erstreckenden, von den Seitenkanten der Rückenlehne (18, 78) nach vorne abstehenden Seitenwänden (20, 22; 80, 82), zusammen mit einer ersten und einer zweiten Führungseinrichtung (24, 26; 84, 86) benachbart dem Übergang zwischen dem Sitzflächenteil (12, 72) und der Rückenlehne (18, 78) zum Lokalisieren des Hüftteils (28) des Erwachsenen-Sicherheitsgurtes, einer Kopfstütze (30, 90), die an der Rückenlehne (18, 78) gelagert ist, und einer dritten Führungseinrichtung (44, 46; 124, 128) für den Schulterteil (48) des Erwachsenen-Sicherheitsgurtes, die derart gelegen ist, daß der Schulterteil (48) des Erwachsenengurtes zwischen der Rückenlehne (18, 78) und der Kopfstütze (30, 90) geführt ist, dadurch gekennzeichnet, daß die Kopfstütze (30, 90) an der Rückenlehne (18, 78) mit Mitteln gelagert ist, die es erlauben, den Bestand zwischen der Kopfstütze (30, 90) und dem Sitzflächenteil (12, 72) einzustellen, und daß die dritte Führungseinrichtung (44, 46; 124, 128) eine Einrichtung (44, 124) zum Beschränken der Bewegung des Schulterteils (48) des Erwachsenen-Sicherheitsgurtes relativ zu der dritten Führungseinrichtung (44, 46; 124, 128) in Querrichtung des Gurts aufweist.
2. Kinder-Sicherheitssitz nach Anspruch 1, bei dem die dritte Führungseinrichtung (44, 46; 124, 128) eine Blockiereinrichtung zum Beschränken der Bewegung des Schulterteils (48) des Erwachsenen-Sicherheitsgurtes relativ zu der dritten Führungseinrichtung (44, 46; 124, 128) in Längsrichtung des Gurtes aufweist.
3. Kinder-Sicherheitssitz nach Anspruch 2, bei dem die Blockiereinrichtung einen Verkeilungs-Nocken (132) aufweist, der so angeordnet ist, daß er eine Bewegung des Schulterteils (48) des Erwachsenen-Sicherheitsgurtes durch die dritte Führungseinrichtung (124, 128) hindurch in die eine Richtung verhindert, während die Bewegung in die entgegengesetzte Richtung möglich ist.
4. Kinder-Sicherheitssitz nach Anspruch 2, bei dem mindestens ein Teil (46) der dritten Führungseinrichtung (44, 46) einen ersten und einen zweiten schwenkbar miteinander verbundenen Grundabschnitt (50, 52), ein Paar parallel beabstandeter

7

EP 0 326 265 B1

8

Ausbildungen (58, 60) an dem zweiten Grundabschnitt (52) und eine komplementäre Ausbildung (56) an dem ersten Grundabschnitt (50), die so ausgebildet ist, daß sie zwischen den parallelen Ausbildungen (58, 60) liegt, um dazwischen einen wellenförmigen Weg zu definieren, wenn der erste und der zweite Grundabschnitt (50, 52) sich in einer ersten relativen Winkelstellung befinden, und von den parallelen Ausbildungen (58, 60) frei ist, wenn der erste und der zweite Grundabschnitt (50, 52) sich in einer zweiten Winkelstellung befinden, zusammen mit einer Rasteinrichtung (62, 64) zum Sichern des ersten und des zweiten Grundabschnitts (50, 52) in deren erster relativer Winkelstellung aufweist.

5. Kinder-Sicherheitssitz nach einem der Ansprüche 1 bis 4, bei dem die Kopfstütze ein Paar Seitenlehnen (32, 34; 92, 94) aufweist und zumindest ein Teil (44, 124, 128) der dritten Führungseinrichtung (44, 46; 124, 128) an einer der Seitenlehnen (32, 34; 92, 94) montiert ist.
6. Kinder-Sicherheitssitz nach einem der Ansprüche 1 bis 5, bei dem eine vierte Führungseinrichtung (44, 46; 124, 128) ähnlich der dritten Führungseinrichtung (44, 46; 124, 128) an der anderen Seitenlehne der Kopfstütze (30, 90) montiert ist.
7. Kinder-Sicherheitssitz nach einem der Ansprüche 1 bis 6, bei dem die Kopfstütze (30) an dem Sitzkörper (10) mittels zweier U-förmiger Gleitstangen (36, 38) gelagert ist, wobei ein Schenkel jeder Gleitstange (36, 38) in der Kopfstütze (30) eingebettet und der andere Schenkel in eine in der Rückenlehne (18) befindliche Führungseinrichtung (42) eingreift.
8. Kinder-Sicherheitssitz nach einem der Ansprüche 1 bis 8, bei dem die Kopfstütze (90) zwei Gleitschuhe (116) aufweist, von denen jeder mit einer zugehörigen Gleitführung (96, 98) in Eingriff steht, die in die Rückenlehne (78) eingelassen ist.
9. Kinder-Sicherheitssitz nach Anspruch 3 und 8, bei dem die dritte Führungseinrichtung (124, 128) einen Schlitz (128) in einem der Gleitschuhe (116) enthält, wobei der Verkellungs-Nocken (132) in dem Schlitz (128) angeordnet ist.

Revendications

1. Un siège de sécurité pour enfant adaptable sur un siège de véhicule, comprenant une ceinture de siège pour adulte comportant un brin d'épaule

(48) et un brin ventral (28), le siège pour enfant comprenant un corps de siège (10, 70) muni d'une assise (12, 72), un dossier (18, 78) et des parois latérales s'étendant verticalement (20, 22; 80, 82), dirigées en saillie vers l'avant à partir des bords latéraux du dossier (18, 78), avec des premiers et des seconds moyens de guidage (24, 26; 84, 86) adjacents à la jonction entre l'assise (12, 72) et le dossier (18, 78), pour positionner le brin ventral (28) de la ceinture de siège pour adulte, un appui-tête (30, 90) monté sur le dossier (18, 78), et des troisièmes moyens de guidage (44, 46; 124, 128) pour le brin d'épaule (48) de la ceinture de siège pour adulte, disposés de manière à guider ledit brin d'épaule (48) de la ceinture pour adulte entre le dossier (18, 78) et l'appui-tête (30, 90), caractérisé en ce que l'appui-tête (30, 90) est monté sur le dossier (18, 78) par des moyens permettant le réglage de la distance entre l'appui-tête (30, 90) et l'assise (12, 72), et que les troisièmes moyens de guidage (44, 46; 124, 128) comprennent des moyens (44, 124) pour limiter le déplacement du brin d'épaule (48) de ladite ceinture pour adulte par rapport aux troisièmes moyens de guidage (44, 46; 124, 128) dans la direction transversale de la ceinture.

2. Un siège de sécurité pour enfant selon la revendication 1, dans lequel les troisièmes moyens de guidage (44, 46; 124, 128) comprennent des moyens de blocage pour limiter le déplacement du brin d'épaule (48) de ladite ceinture de siège pour adulte par rapport aux troisièmes moyens de guidage (44, 46; 124, 128) dans la direction longitudinale de la ceinture.
3. Un siège de sécurité pour enfant selon la revendication 2, dans lequel les moyens de blocage comprennent une came en forme de coin (132), agencée pour empêcher le déplacement du brin d'épaule (48) de ladite ceinture de siège pour adulte à travers les troisièmes moyens de guidage (124, 128) dans une direction, tout en permettant un déplacement dans la direction opposée.
4. Un siège de sécurité pour enfant selon la revendication 2, dans lequel au moins l'élément (46) des troisièmes moyens de guidage (44, 46) comprend des première et seconde parties formant embase (50, 52), réunies entre elles à pivotement, une paire de parties parallèles espacées (58, 60) sur la seconde partie formant embase (52), et une partie complémentaire (56) sur la première partie formant embase (50), agencée de manière à se trouver entre les parties parallèles (58, 60), de manière à définir un trajet sinueux entre elles lorsque les première et seconde parties formant embase (50, 52) sont dans une première

9

EP 0 326 265 B1

10

position angulaire relative et à être dégagée des parties parallèles (58, 60) lorsque les première et seconde parties formant embase (50, 52) sont dans une seconde position angulaire, avec des moyens formant arrêtoir (62, 64) pour bloquer les première et seconde parties de base (50, 52) dans leur première position angulaire relative.

5


5. Un siège de sécurité pour enfant selon l'une quelconque des revendications 1 à 4, dans lequel l'appui-tête comprend une paire de parois latérales (32, 34; 92, 94) et, au moins, une partie (44; 124, 128) des troisièmes moyens de guidage (44, 46; 124, 128) est montée sur l'une des parois latérales (32, 34; 92, 94). 10 15
6. Un siège de sécurité pour enfant selon l'une quelconque des revendications 1 à 5, dans lequel des quatrièmes moyens de guidage (44, 46; 124, 128) similaires aux troisièmes moyens de guidage (44, 46; 124, 128) sont montés sur l'autre paroi latérale de l'appui-tête (30, 90). 20
7. Un siège de sécurité pour enfant selon l'une quelconque des revendications 1 à 6, dans lequel l'appui-tête (30) est monté sur le corps de siège (10) par deux barres de glissement en U (36, 38), une aile de chaque rail de glissement (36, 38) étant encastrée dans l'appui-tête (30) et l'autre aile s'engageant dans les moyens de guidage (42) du dossier (18). 25 30
8. Un siège de sécurité pour enfant selon l'une quelconque des revendications 1 à 6, dans lequel l'appui-tête (90) comprend deux patins de glissement (116), chacun d'eux venant s'engager dans un rail de glissement respectif (96, 98), incorporé dans le dossier (78). 35
9. Un siège de sécurité pour enfant selon les revendications 3 et 8, dans lequel les troisièmes moyens de guidage (124, 128) comprennent une fente (128) ménagée dans l'un des patins de glissement (116), la came en forme de coin (132) étant montée dans ladite fente (128). 40 45

50

55

6

EP 0 326 265 B1



EP 0 326 265 B1




Fig. 3.






Fig. 4.




EP 0 326 265 B1

Fig.5.



EP 0 326 265 B1

Fig. 6.



EP 0 326 265 B1




Fig.7.




Fig.8.